TECHNICAL DATA SHEET

UV Additive

Date: 10-12-2018 Page: 1



DESCRIPTION

Special FX UV Additive is specially designed to help prolong the life-span of fluorescent paint colours. Using a UV additive will not stop fading all together but will prolong the life substantially.



Mix Ratio

Clearcoat 100:5% 100 parts clearcoat to 5% UV Additive 2K colour 100:10% 100 parts 2K colour to 10% UV Additive



Spraying viscosity N/A



Spraygun tips N/A



Number of coats:



Flash off time

UV Additive may slightly increase the flash off time of the clearcoat but not affect the curing.

GENERAL NOTES

UV Additive may be added to clearcoat or 2K direct gloss. Direct gloss requires more UV additive due to it being more susceptible to damage from UV rays. Be aware that all fluorescent colours will fade over time.

IMPORTANT NOTES

The technical data contained herein is based on our present knowledge and we experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.